

CPWplus P Bench Scales

The CPWplus line of industrial scales offers an expanded selection of models with capacities to meet more applications than ever. Easy to use, the CPWplus combines reliability and durability for weighing tasks in material testing, shipping and receiving, office, industrial and agricultural applications. With an RS232 interface, a hold function, and a large display with a remote indicator the CPWplus line gives you a versatile scale for less money.

Technical Specifications

Model	CPWplus 6P	CPWplus 15P	CPWplus 35P	CPWplus 75P	CPWplus 150P	CPWplus 200P
Maximum capacity	13lb/6000g	33lb/15kg	75lb/35kg	165lb/75kg	330lb/150kg	440lb/200kg
Readability	0.005lb/2g	0.01lb/5g	0.02lb/10g	0.05lb/20g	0.1lb/50g	0.1lb/50g
Tare range	Full	Full	Full	Full	Full	Full
Repeatability (S.D.)	2g	5g	10g	20g	50g	50g
Linearity (±)	4g	10g	20g	40g	100g	100g
Platform size	11.8x11.8" / 300x300mm					

General Specifications

Typical stabilisation time	2 Sec
Units of measurement	Kilogram (kg), Carat (ct), Pound (lb), Pound-Ounce (lb-oz)
Interface	RS-232 bi-directional Interface
Operating temperature	0° - 40°C
Compensated temperature	32°F - 104°F
Power supply	6 AA size non-rechargeable batteries in a compartment located in the base or 12VAC 150mA from external adapter
Calibration	Automatic External with user selectable calibration mass
Display	LCD with minimum 25mm digits with weight legends for kg, lb, oz and low battery, stable, zero, net weight and hold symbols, as well as ability to display lb and oz together
Housing	Indicator- Aluminium, Platform- Mild Steel base and stainless steel platform
Overall dimensions (wxdxh)	11.8x11.8x2" / 300x300x50mm

Key Accessories

- RS-232 Cable
- Hard Carry Case with Lock
- Adam Printer
- AdamDU - Data Collection Program
- USB to RS-232 Interface Cable
- Thermal Paper for Adam Printer (5 Pack)



Adam Equipment - offices worldwide

www.adamequipment.com